

TASKI Jontec Matt

Matt floor emulsion

Description

Low gloss floor emulsion for most types of smooth and water resistant hard floors. The low gloss appearance prevents from “optical slipperiness” and the product provides also good resistance to alcohol and disinfectants to make it suitable for a healthcare environment. It ensures reduced maintenance costs to improve productivity.

Key properties

- Unique matting system
- Hard, durable and wear resistant protection
- Good resistance to alcohol and disinfectants vs conventional floor emulsions
- Easy to apply, short drying time

Benefits

- Provides a low gloss, protective layer on most smooth and water resistant, hard floors
- Good resistance to scuff marks and dirt, even under heavy traffic levels
- Particularly suitable for use in healthcare thanks to the alcohol resistance and the matt appearance
- Can be applied with a mop or an applicator. Spreads evenly for perfect leveling

Use instructions

Dosage:

The product is ready to use. Apply undiluted

Application:

Shake well before use. Treat only stripped and thoroughly rinsed and completely dry floors. Treat porous and damaged floors with one of the JohnsonDiversey floor sealers prior to application.

Sparingly pour the product onto the floor and evenly spread it while still wet with a polish applicator in overlapping lanes of 1-1.5m. Allow to dry completely (20-30minutes) before applying additional coats in similar manner. Apply two coats to non-porous, smooth floors. Three coats are usually sufficient for porous floors.

Linoleum: After the first coat has dried, smooth the linoleum floor with a single disc machine equipped with a blue pad, then damp mop and allow to dry completely before applying additional coats.


Top stripping and recoating:

Use a JohnsonDiversey floor top stripper to remove one coat of polish and pick up soiled solution with a scrubber drier or wet vacuum cleaner. Allow to dry completely and apply additional coat(s).

Important:

Shake well before use. To prevent from streaking and slippery floors, always apply a minimum of 20g/m² per coat. Do not dilute or mix with other substances. Do not use on structured plastic (cushioned vinyl) and unsealed wood or cork. Seek advice for use on profiled/studded rubber floors. Do not use outdoors or in wet zones.

F2f



TASKI Jontec Matt

Technical data

- Appearance: Milky white liquid
- Relative density [20°C]: 1.02
- pH-value neat: 8.2 - 8.7
- Coverage: 20-40 ml/m²

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Safe handling:

Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet. Only for professional users / specialists.

Storage Information:

Store in original closed containers and do not store at temperatures below 5°C

Approvals

Tested according to ASTM D-2047 for slip resistance