

# Flowfast Cleaner (wht)

# **Product sheet**

### **Product description**

Flowfast Cleaner is a clear, colourless liquid based on methyl methacrylate (MMA).

Note: Material is delivered in white coloured tins. Formerly named Flowfast Cleaner (new).

### Uses

Flowfast Cleaner is used as a smoothing aid for the application of Flowfast mortar coatings. It is also an excellent agent for cleaning application tools. Smoothing of Flowfast coatings and mortars is considerably facilitated by moistening the trowel now and

Smoothing of Flowfast coatings and mortars is considerably facilitated by moistening the trowel now and again with Flowfast Cleaner during their application.

## **Environment & Health**

Flowfast Cleaner is a solvent free product but has an odour associated with it, ensure adequate ventilation and/or extraction. Follow the appropriate Occupational Health and Safety guidelines applicable to the location where the application is undertaken.

For more information, please refer to the safety datasheets for the individual components.

### Ratio of components

Single component product.

Flowfast Cleaner can be re-used several times. It must be stored and transported in well closed original cans. If it is too heavily soiled with remainders of resin and catalyst, Flowfast Cleaner may form deposit or flakes. The volume of deposit is increased by storage at high temperatures, in which case the Flowfast Cleaner must be disposed of as solid matter. To achieve this, add 10% of Flowfast Cleaner to any uncured and reaming resins and leave to cure.

Note: Do not use Flowfast Cleaner to dilute any resins at any time.

# Colour

Clear

# Solids content

Approx. 100 %

Density Approx. 0.94 kg/litre.

Storage 6 months in unopened pack. Storage temperature between 5°C and 30°C (out of direct sunlight).

Protect from weather and moisture/contaminant ingress.

### Packaging

The product is delivered in the following packs.

Unit

10 kg	(10.6 litres)
30 kg	(31.9 litres)

Any suggested practices or installation specifications for the composite floor or wall system (as opposed to individual product performance specifications) included in this communication (or any other) from Flowcrete UK Ltd constitute potential options only and do not constitute nor replace professional advice in such regard. Flowcrete UK Ltd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise.